





HIGHLIGHTS AT A GLANCE:

- High Resolution Printing at 600 dpi
- Rapid Output/High Productivity
- Over-the-Edge Full Card Printing
- High-capacity Card Feeder
- Includes CardEditor Software
- Supports a variety of Card Encoders



DC-7600

Retransfer print technology is the next level of Direct-to-Card technology. First, the image is printed on a film, then the image is transferred from film to the card. This technique is suitable for edge-to-edge printing, heavy duty printing, improves reliability and thus suitable for a large variety of card types, such as:

- Travel ID cards
- Entry permit cards

Resident cards

- Identity cards
- High quality card applications

• Driving Licenses

• Student cards

• Finance cards

TECHNICAL DATA

| Print Method | Colour dye sublimation retransfer technology |
|-------------------|--|
| Resolution | 600 dpi |
| Print Capability | Single Side, Double Side, Over-the-Edge, photo quality image colour |
| Print Speed | Single Side: 25 sec. Double Side: 55 sec. |
| Interfaces | USB (2.0), Ethernet (10/100) |
| Card Thickness | 0,5 - 1,25 mm (20 - 50 mil) |
| Security Features | RFID ribbon, card feeder lock, custom watermarks (BMP) |
| Card Loading | Auto card feeder for 250 cards (0,76 mm thickness) Manual feed: single card |
| Card Types | PVC, ABS, PET, PET-G, PC 85,6 x 53,98 mm (ISO ID-1/CR-80 size) |
| Consumables | Ribbon YMCK (500 Images), Ribbon YMCKH (400 Images), Ribbon YMCKK (400 Images), Ribbon YMCKI (400 Images), Ribbon YMCKSI (350 Images), Transfer Film YMCK (500 Images) Ribbon K (500 Images), Transfer Film K (500 Images) Ribbon YMCK for PatchIM (500 Images), PatchIM PP (250 Images) |
| Cleaning Set | Cleaning Card Cleaning Roller |
| Physical Weight | 22 kg |
| Physical Size | 339 x 311 x 431 mm (W x D x H) |
| Noise | 55 dB(A) while printing 40 dB(A) in standby |
| Power Voltage | Auto wide ranging, 100 - 240 V AC - 50/60 Hz |
| Environment | Printing: +15° to +30° C Temperature; 35 - 95% Humidity Storage: +5° C to +45° C Temperature; 35 - 95% Humidity |
| Driver | Windows 8/8.1/10/11 and Server 2012/2016/2019/2022 |
| Optional Encoder | Encoder for MIFARE |
| Warranty | For more details please contact your local dealer |





Jiangmen Dascom Computer Peripherals Co., Ltd.
No.399, Jinxing Road | Jianghai District | Jiangmen City
Guangdong Province | CHINA
Tel.: +86 0750-3868008 | Fax: +86 0750-3868011

info.cn@dascom.com | www.dascom.com

APAC
DASCOM AP Pte. Ltd.
2 Jurong East Street 21 | # 05-42, IMM Building Singapore 609601

Tel.: +65 6760 8833 | Fax: +65 67601066 info.sg@dascom.com | www.dascom.com.sg

AMERICAS

DASCOM Americas 34 Lakeview Court | Verona | Virginia, 24482 | USA Tel.: +1 (877) 434-1377 info.us@dascom.com | www.dascomamericas.com

DASCOM Europe GmbH Heuweg 3 | 89079 Ulm | GERMANY Tel.: +49 731 2075-0 | Fax: +49 731 2075-100 info.de@dascom.com | www.dascomeurope.de

